

# ARTICLE DATA SHEET



**Article** : **Oklahoma BO 32mm - Honeycomb Fabrics**  
**Version** : **2024-01**

---

The frontside and backside of this so-called full-tone taffeta black-out fabric have identical colours. The piece dyed woven Oklahoma BO fabric comes in eight contemporary full-tone colours. The tightly-woven fabric has a silver coating on the inside for additional insulation and to prevent light from shining through the fabric.

---

**Composition** : 100% Polyester (PES)  
**Construction** : piece-dyed, film laminated, woven fabric  
**Transparency** : black-out

---

**Oeko-Tex standard 100 certified** : yes  
**Flame retardant** : no  
**Moisture resistant** : yes  
**PVC / Halogen free** : yes

---

**Customs code** : 5407 5200  
**Preferential origin EU** : no

---

**Form of cell** : D-shape  
**Colour** : Full-Tone  
**Cell size** : 32 mm +/- 1,0 mm  
**Plane range** : visual plane +/- 1,0 mm  
**Fabric width** : 300 cm +/- 5 cm  
**Fabric length** : 15,73 meters +/- 10%

---

**Weight per m2** : 297 g/m2 +/- 10%  
**Material thickness** : 0,17 mm +/- 10%  
**Colour fastness** : 5 - 7 DIN EN ISO 105 B02 (blue scale 1-8)

---

**Cupping** : max. 2%  
**Twisting** : max. 2%

---

**Labelling faults** : indicated with a red label  
**Fault definition** : any deviation in product and/or structure visible from 1 meter distance  
**Faults per package** : max. 1 per 10 meters (on average)  
**Mutual fault distance** : min. 2,5 meters between local faults

---

**Pieces per packaging** : max. 2 pieces with a min. length of 200 cells per piece  
**Fabric in packaging** : room side up

---

**Packaging** : corrugated cardboard carton, fabric wrapped around in paper  
**Batch identification** : label on face side of packaging, label on front side of packaging  
**Total weight packaging** : appr. 19,5 kg  
**Packaging dimensions** : 3200 x 300 x 60 mm  
**Packing-list specification** : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.  
**Storage and transport** : horizontal

---

**Cutting recommendation** : guillotine cutter  
**Drilling recommendation** : 3,5 mm diameter hollow drill or 3,0 mm diameter spiral drill

---

*Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on [www.lienesch.com](http://www.lienesch.com).*