ARTICLE DATA SHEET



Article : PALMA BO 45 mm - Honeycomb Fabrics

Version : 2020-01

The insulating honeycomb structure combined with a reflecting white backside makes 100% blackout fabric Palma BO an essential article for every functional collection. The insulating quality of this non-woven fabric is enhanced by the silver coating on the inside of the cells. This 45mm Palma BO is offered in a width of 366 cm. It makes the fabric ideal for larger windows; even with larger dimensions the fabric folds into a thin stack. The 45 mm variety is available in twelve colours.

Composition Construction		100% Polyester (PES) pointbonded non-woven film-laminated fabric	
Transparency	: black-out		
Oeko-Tex standard 100 certified Flame retardant	: yes : no		
Moisture resistant	: yes		
PVC / Halogen free	: yes		
Customs code	: 6307 9098		
Preferential origin EU	: no		
Form of cell	: D-shape		
Colour	: Duo-Tone	. / 4.0	
Cell size Fabric width	: 45 mm : 366 cm	+/- 1,0 mm +/- 5 cm	
Fabric width Fabric length	: 500 cells	+/- 25 cells	
i abiic lengin	17,5 meters	47- 23 GGIIS	
Weight per m2	: 208 g/m2	+/- 10%	
Material thickness	: 0,21 mm	+/- 10%	
Colour fastness	: 4 - 5	DIN EN ISO 105 B02 (grey scale 1-5)	
Cupping	: max. 2%		
Twisting	: max. 2%		
Labelling faults		indicated with a red label	
Fault definition		any deviation in product and/or structure visible from 1 meter distance	
Faults per package Mutual fault distance		max. 1 per 10 meters (on average) min. 2,5 meters between local faults	
	. min. 2,5 meters	min. 2,5 meters between local faults	
Pieces per packaging		max. 2 pieces with a min. length of 200 cells per piece	
Fabric in packaging	: room side up	room side up	
Packaging		corrugated cardboard carton, fabric wrapped around in paper	
Batch identification		label on face side of packaging, label on front side of packaging	
Total weight packaging	: appr. 16,0 kg	appr. 16,0 kg 3800 x 260 x 70 mm	
Packaging dimensions Packing-list specification		article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.	
Storage and transport	: horizontal	<u> </u>	
· · · · · · · · · · · · · · · · · · ·	. auillotina autra		
Cutting recommendation Drilling recommendation		guillotine cutter 3,0 mm diameter hollow drill or 3,5 mm diameter spiral drill	
	. 3,0 mm diamete	i nonow unii oi 3,3 mm diameter spirai unii	

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.