

# ARTICLE DATA SHEET



**Article** : **Pittsburgh BO 32 mm - Honeycomb Fabrics**  
**Version** : **2024-01**

---

Black-out Honeycell fabric Pittsburgh combines an attractive, modern colour pallet with a maximum of functionality. Due to the honeycomb structure, this non-woven 32mm fabric has excellent insulating properties ensuring the heat to stay outside during summer and inside during winter. The smaller cell size allows construction in tight spaces such as on sliding panels or glass doors. True® Pittsburgh BO 32 mm is available in ten colours.

---

Composition : 100% Polyester (PES)  
Construction : spunlace, non-woven, film-laminated fabric  
Transparency : black-out

---

Oeko-Tex standard 100 certified : yes  
Flame retardant : no  
Moisture resistant : yes  
PVC / Halogen free : yes

---

Customs code : 6307 9098  
Preferential origin EU : no

---

Form of cell : D-shape  
Colour : Duo-Tone  
Cell size : 32 mm +/- 1,0 mm  
Fabric width : 300 cm +/- 5 cm  
Fabric length : 15,4 meters +/- 10%

---

Weight per m2 : 165 g/m2 +/- 10%  
Material thickness : 0,2 mm +/- 10%  
Colour fastness : 6 DIN EN ISO 105 B02 (blue scale 1-8)

---

Cupping : max. 2%  
Twisting : max. 2%

---

Labelling faults : indicated with a red label  
Fault definition : any deviation in product and/or structure visible from 1 meter distance  
Faults per package : max. 1 per 10 meters (on average)  
Mutual fault distance : min. 2,5 meters between local faults

---

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece  
Fabric in packaging : room side up

---

Packaging : corrugated cardboard carton, fabric wrapped around in paper  
Batch identification : label on face side of packaging, label on front side of packaging  
Total weight packaging : appr. 12,0 kg  
Packaging dimensions : 3200 x 350 x 50 mm  
Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.  
Storage and transport : horizontal

---

Cutting recommendation : guillotine cutter  
Drilling recommendation : 3,5 mm diameter hollow drill or 3,0 mm diameter spiral drill

---

*Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on [www.lienesch.com](http://www.lienesch.com).*