

ARTICLE DATA SHEET



Article : **True® Halifax BO 25 mm - Honeycomb Fabrics**
Version : 2024-01

Black-out Honeycell fabric True® Halifax BO has the same quality as basic cloth True® Rioja. The fabric has a subtle irregular linear print pattern. Due to its 25 mm cellular structure and white backing, fabric True® Halifax BO has excellent insulation and reflection qualities. This makes the material the perfect combination between functionality and atmosphere. True® Halifax BO is available in ten natural timeless colours. The fabric has a silver coating on the inside for additional insulation.

Composition : 80% Post-consumer recycled polyester / 20% Polyester (PES)
Construction : spunlace non-woven film-laminated fabric + screen print
Transparency : black-out

Oeko-Tex standard 100 certified : yes
Flame retardant : no
Moisture resistant : yes
PVC / Halogen free : yes

Customs code : 6307 9098
Preferential origin EU : no

Form of cell : D-shape
Colour : Duo-Tone
Cell size : 25,4 mm +/- 1,0 mm
Fabric width : 300 cm +/- 5 cm
Fabric length : 12,4 meters +/- 10%

Weight per m2 : 167 g/m2 +/- 10%
Material thickness : 0,17 mm +/- 10%
Colour fastness : 5 DIN EN ISO 105 B02 (blue scale 1-8)

Cupping : max. 2%
Twisting : max. 2%

Labelling faults : indicated with a red label
Fault definition : any deviation in product and/or structure visible from 1 meter distance
Faults per package : max. 1 per 10 meters (on average)
Mutual fault distance : min. 2,5 meters between local faults

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece
Fabric in packaging : room side up

Packaging : corrugated cardboard carton, fabric wrapped around in paper
Batch identification : label on face side of packaging, label on front side of packaging
Total weight packaging : appr. 12,3 kg
Packaging dimensions : 3180 x 280 x 50 mm
Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.
Storage and transport : horizontal

Cutting recommendation : guillotine cutter
Drilling recommendation : 3,5 mm diameter hollow drill

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.