

# ARTICLE DATA SHEET



**Article** : **Westmount FR BO 25 mm - Honeycomb Fabrics**  
**Version** : 2024-01

---

Honeycell fabric Westmount FR BO is not only flame retardant, it is also black-out. This refined non-woven quality has a 25 mm honeycomb structure. The cells have a silver coating on the inside that not only blocks out the light but also provides insulation. It allows the fabric to optimally contribute to a comfortable indoor climate and energy savings during both winter and summer. Westmount FR BO is available in fourteen natural tones and bright colours that match any interior.

---

Composition : 100% Polyester (PES)  
Construction : pointbonded non-woven film-laminated fabric  
Transparency : black-out

---

Oeko-Tex standard 100 certified : yes  
Flame retardant : yes  
Moisture resistant : yes  
PVC / Halogen free : yes

---

Customs code : 6307 9098  
Preferential origin EU : no

---

Form of cell : D-shape  
Colour : Duo-Tone  
Cell size : 25,4 mm +/- 1,0 mm  
Fabric width : 300 cm +/- 5 cm  
Fabric length : 12,4 meters +/- 10%

---

Weight per m2 : 243 g/m2 +/- 10%  
Material thickness : 0,18 mm +/- 10%  
Colour fastness : 4 - 5 DIN EN ISO 105 B02 (grey scale 1-5)

---

Cupping : max. 2%  
Twisting : max. 2%

---

Labelling faults : indicated with a red label  
Fault definition : any deviation in product and/or structure visible from 1 meter distance  
Faults per package : max. 1 per 10 meters (on average)  
Mutual fault distance : min. 2,5 meters between local faults

---

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece  
Fabric in packaging : room side up

---

Packaging : corrugated cardboard carton, fabric wrapped around in paper  
Batch identification : label on face side of packaging, label on front side of packaging  
Total weight packaging : appr. 14,6 kg  
Packaging dimensions : 3180 x 280 x 50 mm  
Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.  
Storage and transport : horizontal

---

Cutting recommendation : guillotine cutter  
Drilling recommendation : 3,5 mm diameter hollow drill

---

*Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on [www.lienesch.com](http://www.lienesch.com).*