

ARTICLE DATA SHEET



Article : **PALMA BO 20 mm - Honeycomb Fabrics**
Version : 2019-01

The insulating honeycomb structure combined with a reflecting white backside makes 100% blackout fabric Palma BO an essential article for every functional collection. The insulating quality of this non-woven fabric is enhanced by the silver coating on the inside of the cells. In addition to in a 25 mm single-cell variety, Palma BO is also available in a unique 20 mm variety. Both varieties are available in a width of no less than 300 cm. making the fabric ideal for larger windows; even with larger dimensions the fabric folds into a thin stack. The 20 mm variety is available in twelve colours.

Composition : 100% Polyester (PES)
Construction : point bonded, non-woven, film-laminated fabric
Transparency : black-out

Oeko-Tex standard 100 certified : yes
Flame retardant : no
Moisture resistant : yes
PVC / Halogen free : yes

Customs code : 6307 9098
Preferential origin EU : no

Form of cell : O-shape (running change)
Colour : Duo-Tone
Cell size : 20,0 mm +/- 1,0 mm
Fabric width : 300 cm +/- 5 cm
Fabric length : 8,5 meters +/- 10%

Weight per m2 : 190 g/m2 +/- 10%
Material thickness : 0,18 mm +/- 10%
Colour fastness : 5 - 6 DIN EN ISO 105 B02 (blue scale 1-8)

Cupping : max. 2%
Twisting : max. 2%

Labelling faults : indicated with a red label
Fault definition : any deviation in product and/or structure visible from 1 meter distance
Faults per package : max. 1 per 10 meters (on average)
Mutual fault distance : min. 2,5 meters between local faults

Pieces per packaging : max. 2 pieces with a min. length of 200 cells per piece
Fabric in packaging : room side up

Packaging : corrugated cardboard carton, fabric wrapped around in paper
Batch identification : label on face side of packaging, label on front side of packaging
Total weight packaging : appr. 9,2 kg
Packaging dimensions : 3180 x 290 x 40 mm
Packing-list specification : article nr. / colour nr. / batch nr. / gross- and net linear meters / PO nr.
Storage and transport : horizontal

Cutting recommendation : guillotine cutter
Drilling recommendation : 3,0 mm diameter hollow drill or 3,5 mm diameter spiral drill

Text changes, technical modifications and misprints reserved. All our transactions are subject to our General Terms and Conditions that can be consulted free of charge on www.lienesch.com.